



AC VSF

Vinyle solin intégré en dôme acrylique - fixe

Tableau des tailles impériales

AC VSF Solins vinyle intégré en dôme acrylique - fixe										
Modèle		2020	2028	2036	2052	2076	2828	2836	2840	2852
Ouverture du toit (LxH)	po.	14.5 x 14.5	14.5 x 22.5	14.5 x 30.5	14.5 x 46.5	14.5 x 70.5	22.5 x 22.5	22.5 x 30.5	22.5 x 34.5	22.5 x 46.5
Surface vitrée	pi ²	1.46	2.27	3.07	4.68	7.10	3.52	4.77	5.39	7.27

AC VSF Solins vinyle intégré en dôme acrylique - fixe										
Modèle		2860	2864	2868	2876	3280	3636	3652	3660	3664
Ouverture du toit (LxH)	po.	22.5 x 54.5	22.5 x 58.5	22.5 x 62.5	22.5 x 70.5	26.5 x 74.5	30.5 x 30.5	30.5 x 46.5	30.5 x 54.5	30.5 x 58.5
Surface vitrée	pi ²	8.52	9.14	9.77	11.02	13.71	6.46	9.85	11.54	12.39

AC VSF Solins vinyle intégré en dôme acrylique - fixe								
Modèle		3668	3676	4040	4052	4064	4242	5252
Ouverture du toit (LxH)	po.	30.5 x 62.5	30.5 x 70.5	34.5 x 34.5	34.5 x 46.5	34.5 x 58.5	36.5 x 36.5	46.5 x 46.5
Surface vitrée	pi ²	13.24	14.93	8.27	11.14	14.02	9.25	15.02

- Tous les puits de lumière peuvent être installés verticalement ou horizontalement, i.e. 3652 peut devenir 5236.
- Toit de bardeaux seulement, avec un minimum de pente de 3:12 (14°).